

IMPROVED POLYURETHANE/GEOTEXTILE COMPOSITE AND
A PROCESS RELATED THERETO FOR THE PRODUCTION THEREOF

TECHNICAL FIELD OF THE INVENTION

The present invention relates to an improved polyurethane geotextile composite prepared with an unfilled polyurethane composition. The invention further relates to a process of forming a polyurethane geotextile composite using an unfilled polyurethane composition.

BACKGROUND OF THE INVENTION

In recent years, the management of natural resources has become important in many countries throughout the world. Efforts have been directed both toward the conservation of our resources and toward the elimination of pollution from our environment. Particular emphasis has been placed on waste leakage and water loss.

Losses in the distribution of water using unlined irrigation ditches are estimated at a minimum to be 25% and in some situations to be more than 50% depending upon the porosity of the ditch surface and the distance the water is being moved. In most rural areas, ditches are formed by excavating the soil to the desired depth and width. The water moves through the ditch in contact with the exposed natural surface. This can be sand, clay, rocks, etc. and, more commonly, mixtures thereof. The porosity will depend upon the proportions of the different components.

The loss of water in unlined irrigation ditches at one time was considered acceptable only because the supply of water exceeded demand. However, as civilization has developed and world population has increased, more water is required for both greater food production and for the markedly by increasing non-agriculture uses. In addition to greater domestic uses in sanitation, industry now employs large quantities of water in manufacturing and processing procedures.

"Express Mail" mailing label number EK633384415US
Date of Deposit March 15, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner of Patents and Trademarks, Washington, D.C. 20231

Donna J. Veatch
(Name of person mailing paper or fee)


Signature of person mailing paper or fee)

This high level of consumption plus the very high cost of developing new water supplies has shifted attention to water conservation. Domestic appliances that use less water have been developed. Also, industry has installed recycling purification systems to reduce water consumption.

5 Although conservation efforts have reduced water consumption to a degree, water is still in relatively short supply, particularly in recent years with the severe droughts in the United States and other countries. Since the most cost effective conservation opportunities and readily accessible water supplies already have been developed, greater attention must be
10 directed to improving the efficiency of water distribution systems.

Improvements in water distribution have been made. A limited number of ditches and canals have been lined with concrete and/or preformed concrete pipes. Concrete is durable and has a long life when properly used. However, concrete is expensive to place and finish and is
15 damaged by unfavorable temperatures during curing. Also, concrete is subject to frost damage, cracking and heaving which results in leaks.

Processes for forming polyurethane composite liners for canals and ditches and apparatus to perform such processes are disclosed, for example, in United States Patent Nos. 4,872,784; 4,955,759; 4,955,760;
20 5,049,006; 5,062,740; 5,421,677; and 5,607,998.

United States Patent No. 5,421,677 ("the '677 patent") is directed to an improved process of forming a ditch liner. The mixture of the '677 patent includes one or more fillers in an amount of up to 60% by weight based upon the total weight of the mixture. The mixture is dispensed on a
25 geotextile, thereby forming a liquid filler-containing polyurethane soaked geotextile composite. The liquid polyurethane soaked geotextile composite is then placed over the surface of an area to be lined. One drawback of the mixture taught by the '677 patent is that the filler in the mixture does not completely dry, especially when stored and used in an
30 outdoor application. The water in the filler reacts with the polyisocyanate

and causes the mixture to foam. Foaming weakens the strength and impermeability of the composite.

For the foregoing reasons, it would be desirable to develop an improved polyurethane composition for producing a polyurethane geotextile composite, specifically, a polyurethane composition that does not include a filler.

SUMMARY OF THE INVENTION

The invention is directed to an improved geotextile composite useful as a liner for canals and ditches and to a process for making a canal or ditch liner with such composite. The composite is made up of a geotextile impregnated with an unfilled polyurethane composition, the unfilled polyurethane composition comprising a reaction product of:

- a) a liquid polyisocyanate having an isocyanate content of at least 10% by weight,
- b) an isocyanate reactive component comprising one or more polyether polyols having from 2 to 6 hydroxyl groups and a number average molecular weight of at least 250 to 8,000 and 0 to 10% by weight, based on total weight of b), of a low molecular weight diol or triol having an equivalent weight of 31 to 99, and
- c) an organometallic catalyst.

The invention is further directed to a canal or ditch lined with the improved polyurethane geotextile composite.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows the surface of the polyurethane casting produced in Example 1 as seen with a scanning electron microscope.

Figure 2 shows the surface of the polyurethane casting produced in Example 2 as seen with a scanning electron microscope.

Figure 3 shows the surface of the polyurethane casting produced in Example 3 as seen with a scanning electron microscope.

DETAILED DESCRIPTION OF THE INVENTION

The present invention is directed to an improved polyurethane/
geotextile composite prepared with an unfilled polyurethane composition,
the process for producing such composite and to a ditch or canal lined with
5 such composite.

The improved geotextile composite liner which is suitable for canals
and ditches is a geotextile impregnated with an unfilled polyurethane
composition, the unfilled polyurethane composition comprising a reaction
product of:

- 10 a) a liquid polyisocyanate having an isocyanate content
of at least 10% by weight, preferably at least 20% by weight,
most preferably, at least 30% by weight,
- b) an isocyanate reactive composite comprising one or
15 more high molecular weight polyether polyols having
from 2 to 6 hydroxyl groups and a number average
molecular weight of at least 250 to 8,000 and from 0 to 10%
by weight, based on total weight of b), of a low molecular
weight diol or triol having an equivalent weight of 31 to 99,
and
- 20 c) an organometallic catalyst, preferably in an amount of up to
0.5 parts by weight per hundred parts by weight of
component b), more preferably from 0.0001 to 0.05 parts by
weight catalyst per 100 parts by weight of component b).

As used herein, the term "unfilled polyurethane composition" means
25 a polyurethane produced from a reaction mixture which does not include
any filler materials.

A canal or ditch is lined with the improved polyurethane geotextile
composite by impregnating a geotextile with an unfilled polyurethane
composition, laying the polyurethane-impregnated geotextile onto a
30 surface of a canal or ditch before the polyurethane composition has fully
cured, conforming the polyurethane-impregnated geotextile to the shape of

the surface of the canal or ditch, and allowing the polyurethane composite to fully cure to form a leakproof liner.

In a preferred embodiment of the invention, the geotextile is impregnated with an unfilled polyurethane composition which is a reaction product of

- a) a liquid polyisocyanate having an isocyanate content of at least 10% by weight,
- b) a polyol mixture comprising:
 - i) from 5 to 15 parts by weight of a propylene oxide adduct of an amine containing starting component, having a molecular weight of from 250 to 1000, preferably from 400 to 600,
 - ii) a propylene oxide adduct of a low molecular weight organic compound having from 3 to 6 OH groups (preferably having 3 or 4 OH groups), and having a molecular weight of from 250 up to 1000, preferably from 600 to 800, and
 - iii) a propylene oxide adduct of a low molecular weight diol having a molecular weight of from 250 up to 3000, and
- c) a tin catalyst.

The above-described composition used in the preferred embodiment of the invention cures in a reasonable amount of time without application of any externally applied heat and under temperature conditions varying from 0°C to 50°C. It is, of course, possible to accelerate the curing of the polyurethane by any of the techniques known to those in the art but such acceleration is not necessary.

The various materials used in the composition of the present invention are known in the art. The polyurethane-forming composition of the present invention requires a) a liquid isocyanate having an isocyanate

content of at least 10% by weight, b) at least one polyether polyol, and c) a catalyst.

As used herein, the term "geotextile" refers to any woven or non-woven porous blanket or mat which is produced from natural or synthetic fibers. Also, as used herein, the term "ditch" and "canal" are used interchangeably and can refer to any liquid-carrying surface having a depression or sloped side. Geotextiles are used primarily to line earthen surfaces. Such liners may have secondary uses in lining roofs, ponds, reservoirs, landfills, and underground storage tanks, canals or ditches.

Examples of geotextiles include woven or non-woven polypropylene, polyester, jute and cotton fabrics.

The isocyanates useful herein are known. Suitable organic polyisocyanates include aliphatic, cycloaliphatic, araliphatic, aromatic, and heterocyclic polyisocyanates of the type described, for example, by W.

Siefken in Justus Liebigs Annalen der Chemie, 562, pages 75 to 136. Such isocyanates include those represented by the formula $Q(NCO)_n$ in which n represents a number from 2 to about 5 (preferably 2 to 3) and Q represents an aliphatic hydrocarbon group containing from 2 to about 18 (preferably 6 to 10) carbon atoms, a cycloaliphatic hydrocarbon group containing from 4 to about 15 (preferably 5 to 10) carbon atoms, an araliphatic hydrocarbon group containing from 8 to 15 (preferably 8 to 13) carbon atoms, or an aromatic hydrocarbon group containing from 6 to about 15 (preferably 6 to 13) carbon atoms. Examples of suitable isocyanates include ethylene diisocyanate; 1,4-tetramethylene diisocyanate; 1,6-hexamethylene diisocyanate; 1,12-dodecane diisocyanate; cyclobutane-1,3-diisocyanate; cyclohexane-1,3-and 1,4-diisocyanate, and mixtures of these isomers; 1-isocyanato-3,3,5-trimethyl-5-isocyanatomethylcyclohexane ("isophorone diisocyanate"; See, e.g., German Auslegeschrift 1,202,785 and U.S. Patent No. 3,401,190); 2,4- and 2,6-hexahydrotoluene diisocyanate and mixtures of these isomers; dicyclohexylmethane-4,4'-diisocyanate ("hydrogenated MDI", or "HMDI");

1,3- and 1,4-phenylene diisocyanate; 2,4- and 2,6-toluene diisocyanate and mixtures of these isomers ("TDI"); diphenylmethane-2,4'-and/or -4,4'-diisocyanate ("MDI"); naphthylene-1,5-diisocyanate; triphenylmethane-4,4',4"-trisocyanate; polymethylene poly(phenyl-isocyanates) of the type

5 which may be obtained by condensing aniline with formaldehyde, followed by phosgenation ("crude MDI"), which are described, for example, in British Patents 878,430 and 848,671; norbornane diisocyanates, such as described in U.S. Patent No. 3,492,330; m- and p-isocyanatophenyl sulfonylisocyanates of the type described in U.S. Patent No. 3,454,606;

10 perchlorinated aryl polyisocyanates of the type described, for example, in U.S. Patent No. 3,227,138; modified polyisocyanates containing carbodiimide groups of the type described in U.S. Patent No. 3,152,162; modified polyisocyanates containing urethane groups of the type described, for example, in U.S. Patent Nos. 3,394,164 and 3,644,457;

15 modified polyisocyanates containing allophanate groups of the type described, for example, in British Patent 994,890, Belgian Patent 761,616, and published Dutch Patent Application 7,102,524; modified polyisocyanates containing isocyanurate groups of the type described, for example, in U.S. Patent No. 3,002,973, German Patentschriften

20 1,022,789, 1,222,067 and 1,027,394, and German Offenlegungsschriften 1,919,034 and 2,004,048; modified polyisocyanates containing urea groups of the type described in German Patentschrift 1,230,778; polyisocyanates containing biuret groups of the type described, for example, in German Patentschrift 1,101,394, U.S. Patent Nos. 3,124,605

25 and 3,201,372, and in British Patent 889,050; polyisocyanates obtained by telomerization reactions of the type described, for example, in U.S. Patent No. 3,654,106; polyisocyanates containing ester groups of the type described, for example, in British Patents 965,474 and 1,072,956, in U.S. Patent No. 3,567,763, and in German Patentschrift 1,231,688; reaction

30 products of the above-mentioned isocyanates with acetals as described in German Patentschrift 1,072,385; and polyisocyanates containing

polymeric fatty acid groups of the type described in U.S. Patent No. 3,455,883. It is also possible to use the isocyanate-containing distillation residues accumulating in the production of isocyanates on a commercial scale, optionally in solution in one or more of the polyisocyanates

5 mentioned above. It is also possible to use mixtures of the polyisocyanates described above.

In general, it is preferred to use readily available polyisocyanates, such as 2,4- and 2,6-toluene diisocyanates and mixtures of these isomers ("TDI"); polymethylene (polyphenylisocyanates) of the type obtained by
10 condensing aniline with formaldehyde, followed by phosgenation ("crude MDI"); and polyisocyanates containing carbodiimide groups, urethane groups, allophanate groups, isocyanurate groups, urea groups, or biuret groups ("modified polyisocyanates"). The commercially available
15 phosgenation products of aniline/formaldehyde condensates are the most preferred isocyanates to be used in the present invention.

The liquid polyisocyanates useful in the present invention have an isocyanate group content of at least 10% by weight, preferably more than 20% by weight and most preferably more than 30% by weight. Aromatic polyisocyanates are preferred. Particularly preferred polyisocyanates are
20 liquid polymethylene poly(phenylisocyanates) having an NCO content of from about 30 to about 33% and a viscosity of from about 20 to 2,000 mPa·s at 25°C.

Suitable polyether polyols for use in component b) include polyethers prepared, for example, by the polymerization of epoxides such
25 as ethylene oxide, propylene oxide, butylene oxide, tetrahydrofuran, styrene oxide, or epichlorohydrin, optionally in the presence of Lewis acids such as BF₃, or prepared by chemical addition of such epoxides, optionally added as mixtures or in sequence, to starting components containing
30 reactive hydrogen atoms, such as water, alcohols, or amines. Examples of starting components include ethylene glycol, 1,3- or 1,2-propanediol, 1,2-, 1,3-, or 1,4-butanediol, trimethylolpropane, 4,4'-dihydroxydiphenylpropane,

aniline, ammonia, ethanolamine, and ethylene diamine. Sucrose polyethers of the type described, for example, in German Offenlegungsschriften 1,176,358 and 1,064,938 may also be used.

Polyethers which contain predominantly primary hydroxyl groups (up to
5 about 90% by weight, based on all of the hydroxyl groups in the polyether) are also suitable. Polyethers modified by vinyl polymers of the kind obtained, for example, by the polymerization of styrene and acrylonitrile in the presence of polyethers (e.g., U.S. Patent Nos. 3,383,351, 3,304,273, 3,523,093, and 3,110,695 and German Patent 1,152,536) are also
10 suitable, as are polybutadienes containing hydroxyl groups. Particularly preferred polyether polyols include polyoxyalkylene polyether polyols, such as polyoxyethylene diol, polyoxypropylene diol, polyoxybutylene diol, and polytetramethylene diol, as well as polyoxypropylene polyoxyethylene triols.

15 Other suitable polyether polyols for use as component b) include the so-called "PHD polyols", which are prepared by reaction of an organic polyisocyanate, hydrazine, and a polyether polyol. U.S. Patent No. 3,325,421 discloses a method for producing suitable PHD polyols by reacting a stoichiometric or substoichiometric quantity (relative to diamine)
20 of polyisocyanate dissolved in a polyol having a molecular weight of at least 500 and a hydroxyl number of no more than 225. See also U.S. Patent Nos. 4,042,537 and 4,089,835.

Suitable polyether polyols for use as component b) also include the so-called "polymer polyols", which are prepared by polymerizing styrene
25 and acrylonitrile in the presence of a polyether. See, for example, U.S. Patent Nos. 3,383,351, 3,304,273, 3,523,093, 3,652,639, 3,823,201 and 4,390,645. Particularly preferred polyols are polyoxypropylene polyethers having a number average molecular weight of from about 400 to about 4,000 and an average hydroxy functionality of from 2 to 3.

30 The most preferred polyethers are polyoxypropylene polyethers that do not contain ethylene oxide units.

It is also preferred that isocyanate reactive component b) contain no more than 0.5% by weight water, most preferably no more than 0.1% by weight water prior to reaction with the polyisocyanate.

The most preferred polyol component b) is a mixture of three components: (1) a propylene oxide adduct of an amine containing starting component which adduct has a molecular weight of from about 250 to about 1000 (preferably from about 400 to about 600), (2) a propylene oxide adduct of a low molecular weight organic compound which adduct has from 3 to 6 OH groups and a molecular weight of from about 250 to 1000 (preferably from 600 to 800), and (3) a propylene oxide adduct of a low molecular weight diol which adduct has a molecular weight of from about 250 to 3000 (preferably from 1500 to 2500). This mixture generally contains from 5 to 15 parts by weight of the amine-initiated adduct (1). The amounts of adducts (2) and (3) are such that the average OH functionality of these adducts is more than 2 but less than 2.8.

Up to 10% by weight, based on total isocyanate-reactive component b), of a low molecular weight (number average molecular weight less than 250) diol or triol having an equivalent weight of from 31 to 99 may optionally be included in the isocyanate reactive component. However, it is preferred, that no such low molecular weight diol or triol be included.

The polyurethane-forming reaction mixture also contains a catalyst c) for catalyzing the reaction between isocyanate groups and hydroxyl groups (i.e., a urethane catalyst). Such catalysts are known in the art. Suitable catalysts are organometallic compounds, preferably organic tin compounds. Organic tin(II) salts of carboxylic acids such as tin(II) acetate, tin(II) octoate, tin(II) ethyl hexoate and tin(II) laurate and tin(IV) compounds such as dibutyl tin oxide, dibutyl tin dichloride, dibutyl tin diacetate, dibutyl tin dilaurate, dibutyl tin maleate, dioctyl tin diacetate and the like are particularly useful. The catalyst is generally used in an amount of from

about 0.0001 to about 0.05 parts by weight per 100 parts by weight of isocyanate-reactive component b).

5 The polyurethane-forming reaction mixture should not contain a catalyst which would catalyze the reaction between an isocyanate group and water. The relative amounts of the liquid polyisocyanate component and isocyanate-reactive component used to produce the unfilled polyurethane composition are such that the NCO/OH equivalent ratio is from 1.4:1 to 0.9 to 1.0, preferably from 1.1:1.0 to 1.0:1.0.

10 The improved polyurethane composition of the present invention can be applied to one or more geotextiles for lining a ditch and/or canal. As used herein, the term "geotextile" refers to any woven or non-woven porous blanket or mat which is produced from natural or synthetic fibers.

15 In one embodiment of the present invention, the ditch and/or canal is lined using a machine such as that described in U.S. Patent Number 5,639,331 ("the '331 patent"). The '331 patent teaches a mobile ditch lining apparatus comprising reservoirs for supplying raw materials such as resin, catalysts, colors or other additives. The reservoirs are connected to a mixing chamber through flexible conduit means. The delivery rate of the raw materials to the mixing chamber varies depending upon the particular
20 formulation and quantity thereof required for a specific incremental area of the liner being formed. The components used to produce the unfilled polyurethane composition employed in the present invention are mixed in the mixing chamber.

25 From the mixing chamber, the unfilled polyurethane composition is applied to one or more geotextiles. The geotextile is pulled from a vat containing the unfilled polyurethane composition through an adjustable die. The opening of the die provides even distribution of the polyurethane reaction mixture on the geotextile, determines how much polyurethane is dispensed on the geotextile, and also controls the thickness of the
30 polyurethane-soaked geotextile composite. The polyurethane-soaked geotextile is then cut to the desired length and placed in the canal or ditch

where it conforms to the surface and cures to form a polyurethane geotextile composite liner. Installing the polyurethane soaked or impregnated geotextile liner should be done in such a way that the end of one piece or section of the geotextile overlaps to a certain extent the end of the adjacent piece or section of geotextile to assure that after curing a
5 seamless permanent flexible polyurethane composite liner is obtained.

In another embodiment of the present invention, the unfilled polyurethane composition is applied to the geotextile by spraying using commercially available two-component polyurethane spray equipment.
10 The polyurethane impregnated geotextile is subsequently placed in the ditch or canal to be lined where it conforms to the surface and cures to form a polyurethane geotextile composite. The geotextile can also first be cut to size and placed in the canal or ditch before the unfilled polyurethane composition is sprayed onto it. Preferably, the geotextile impregnated with
15 the polyurethane is rolled, e.g., with a paint roller, to allow the polyurethane to penetrate through the geotextile to the surface of the ditch or canal while the polyurethane is still liquid. It is also feasible to first spray the unfilled polyurethane onto one geotextile and then apply another geotextile over the first polyurethane impregnated geotextile.

In another embodiment of the invention, the unfilled polyurethane composition is first sprayed on the concrete (even if cracked or broken) of a concrete lined ditch and subsequently a geotextile is placed over the sprayed concrete so that the geotextile will absorb the still liquid polyurethane which will subsequently cure to form a solid yet flexible
20 polyurethane/geotextile composite.

State of the art sprayable polyurethane formulations are not useful in the present invention because they exhibit gel times of only several seconds. In order to prepare the polyurethane geotextile composites of the present invention, using an unfilled polyurethane composition, gel times of
25 at least five minutes, preferably more than 10 minutes are required.

If additional layers of polyurethane composite are desirable, any of the above-described application processes can be repeated one or more times.

5 The thickness of the polyurethane geotextile composite can be varied over a wide range but usually measures from about 50 microns to about 500 microns.

The amount of polyurethane applied to the geotextile(s) can be varied but usually the polyurethane applied per square meter of geotextile ranges from 1 kg to 20 kg, preferably from 2 kg to 5 kg.

10 If desirable, several layers of the polyurethane impregnated geotextile(s) may be applied over each other to obtain a composite of higher strength and dimensional stability. This is actually the preferred mode for lining an earthen canal or ditch.

15 The invention is further illustrated but is not intended to be limited by the following Examples in which all parts and percentages are by weight, unless otherwise specified.

EXAMPLES

The following materials were used in the Examples.

20 Isocyanate A: polymethylene poly (phenylisocyanate) having an NCO content of about 31.5%, a functionality of 2.6 and a viscosity at 25°C of 200 mPa·s.

25 Polyol 1: a monoethanolamine-started propylene oxide polyether polyol, having an OH number of about 350, a functionality of about 3 and a number average molecular weight of about 480.

Polyol 2: a glycerine-started propylene oxide polyether polyol, having an OH number of about 250, a functionality of about 3 and a number average molecular weight of about 670.

30 Polyol 3: a propylene glycol-started propylene oxide having an OH number of 56, a functionality of about 2 and a

number average molecular weight of about 2000.

Catalyst A:

Dimethyltin dilaurate, commercially available as Fomrez UL-28 from Witco.

The following polyol blend was used in the Examples:

- 5 Polyol Blend A: 10 pbw Polyol 1
 45 pbw Polyol 2
 45 pbw Polyol 3
 0.01 pbw Catalyst A

- 10 The polyurethane castings of Examples 1 and 2 were prepared by the following procedure. The procedure for Example 3 was identical, with the exception that no filler (i.e., rubber crumbs) was mixed with Polyol Blend A or otherwise included in the polyurethane composition.

- 15 60 g of rubber crumbs were thoroughly mixed with 140 g of Polyol Blend A. 61.1 g of Isocyanate A were then added and the reaction mixture was hand mixed at 25-30°C for about 2 minutes. The mixture was then poured into a mold (6 in. x 6 in. x 0.125 in.) at room temperature, and the samples were allowed to cure at room temperature for 16 hours before demolding. The samples were stored for at least 1 week at room temperature in a temperature and humidity controlled environment and
20 then tested for various physical and mechanical properties. The results are shown in the Table. The rubber crumbs used in Example 1 were stored at ambient temperature under humid conditions (humidity >80%) for 16 hours. The rubber crumbs used in Example 2 were thoroughly dried in an oven at 110°C for 16 hours before use.

Table

	Example 1	Example 2	Example 3
Polyol Blend A (grams)	140	140	140
Isocyanate A (grams)	61.1	61.1	61.1
Rubber crumbs (grams)	60	60	-
Isocyanate Index	105	105	105
Tensile Strength (psi)	194.3	1235.7	1479
Elongation (%)	59.2	63.1	75.2
Split Tear (pli)	8.7	38.4	43
Die "C" Tear	34	145.9	155
Water Vapor Transmission	0.2	0.05	0.08

5 The unfilled polyurethane composition within the scope of the present invention (Example 3), had superior properties when compared to the filled systems illustrated in Examples 1 and 2. The wet rubber crumbs used in Example 1 caused severe foaming and also led to a loss in physical properties of the resulting polyurethane. Figure 1 shows the micro-bubbles formed by the reaction of the isocyanate with the water present in the rubber crumbs used. The filled polyurethane made with the dry filler in Example 2 did not exhibit the severe foaming of the composition of Example 1, however, micro-defects caused by the rubber particles which can be seen in Figure 2, cause a weakening of the polyurethane. Under actual application conditions outdoors it is not feasible to dry the filler or to keep a pre-dried filler from absorbing moisture on the surface. Predrying the filler for an extended period of time at high temperatures also has a negative impact on the economics of the composite liner system.

20 The foaming and micro-defects in the polyurethanes of Examples 1 and 2 seen in Figures 1 and 2, are not, however, experienced in the unfilled polyurethane made in Example 3 as is evident from Figure 3.

Example 4

Isocyanate A, and Polyol Blend A were delivered to a mixing chamber at an Isocyanate Index of 105 and applied to a geotextile using the device disclosed in U.S. Patent 5,639,331. The impregnated

geotextile was then cut to the desired length and placed in an earthen ditch in a manner such that the impregnated geotextile covered the entire surface area of the ditch but did not overlap the "lip" or "edge" of the ditch. Any wrinkles or irregularities were smoothed before the polyurethane

5 cured. The polyurethane was allowed to cure under ambient conditions. The ditch liner thus formed was very effective in conveying captured rain water without significant loss due to seepage or leakage.

Although the invention has been described in detail in the foregoing for the purpose of illustration, it is to be understood that such detail is

10 solely for that purpose and that variations can be made therein by those skilled in the art without departing from the spirit and scope of the invention except as it may be limited by the claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197